



TECHNICAL DATA SHEET - DIGITAL PRINTING - ANTI-GRAFFITI - PERMANENT ADHESIVE
AG 700

Film composed of a 36- μ m polyester, which is coated with a pressure-sensitive acrylic adhesive. Glossy surface finish for cold lamination.

FILM FEATURES:

	<u>Average values</u>	<u>Standard</u>
• Thickness (μ m):	36	
• Tensile strength (N/25 mm):	> 100	HEXNFX41021
• Shrinkage 168 hours at +70 °C (+158 °F) (mm):	< 0.2	HEXRET001
• Surface roughness (μ m):	< 5*	HEXRUG001

* A surface roughness less than 10 μ m indicates a floor that can be potentially hazardous in wet conditions. Do not apply to floors.

LINER:

- Silicone-coated paper 80 g/m², with grey HEXIS print.
- Stable under hygrometric variations.

ADHESIVE PROPERTIES:

(Measured average values at publication of the technical data sheet)

	<u>Average values</u>	<u>Standard</u>
• Peel strength test 180° on glass (N/25 mm):		HEXFTM001
after 20 minutes of application	13	
after 24 hours of application	14	
• Initial tack (N/25 mm):	19	HEXFTM009
• Release (N/25 mm):	0.20	HEXFTM003
• Resistance to solvents: the adhesive is resistant to most chemicals (alcohol, diluted acids, oils, ketones).		

ADHESIVE:

- Solvent-based acrylic (adhesive non-repositionable).
- Immediate and permanent adhesion, suitable for wet application.

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +10 °C
- Operating temperature range: -40 °C to +90 °C (-40 °F to +194 °F).
- The film can be cleaned using non-abrasive accessories, with acetone, alcohol, soapy water or HEX'AG.
- In the case of already painted substrate, self-adhesive media must only be applied to undamaged original paintwork. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 2 years when stored upright in its original packaging in a dustfree environment at a temperature ranging from +15 °C and +25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

DURABILITY: (Central European climate)

- Vertical outdoor exposure:
Film without graffiti, not cleaned using solvents: 3 years.
Cleaned film: dependent on the method and frequency of cleaning.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.